

M-Bus to LoRaWAN IoT converter, externally powered

ACR-CV-101L-M-EAC

ACR-CV-101L-M-EDC

M-Bus to LoRaWAN converter finds its application mainly in the reading of electricity meters and calorimeters. The M-Bus converter supports connections of up to 5 UL (Unit Loads) and communication is based on the EN 137 57-3 protocol.

Key selling points:

- Readings of up to 5UL
- Master or Slave device type
- Communication speed 300 - 9600Bd
- LUA scripting interface
- External power supply AC or DC
- External SMA antennas for high gains



M-Bus interface	
Device type:	Master or Slave
Communication speed:	300 - 9600Bd
Maximum connected devices:	5 UL (Unit Loads. 1UL = 1.5 mA)
M-Bus protocol:	EN 137 57-3
LPWAN communication	
LoRaWAN	1.0.1
Registration method:	OTAA or ABP
Frequency:	868MHz, other on request
TX Power:	12,7dBm
Configuration:	Over the cable via GUI or downlinks
General information	
Power supply:	85- 305 VAC or 9 – 36 VDC
IP coverage:	IP65
Dimensions:	145 x 90 x 55 mm
Operational temperature:	-30 °C to +60 °C
Weight:	250 g
Mounting:	Wall / Pole
HS code	85269200